

# Bon<sup>®</sup>

## SAFETY DATA SHEET

### #32-305 CONCENTRATED CONCRETE CLEANING DETERGENT

---

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: Bon Tool Co.  
DBA Bonway  
4430 Gibsonia Rd.  
Gibsonia, PA 15044

In case of transportation of chemical  
emergency contact:

Telephone: 724-443-7080  
Toll Free: 800-444-7060  
Fax: 724-443-7090  
www.bontool.com

ChemTel, Inc.  
1-800-255-3924 (24 hours)

Product Use: Hard surface cleaner  
Not recommended for:

#### 2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

##### GHS Ratings:

Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: $\geq 1.5 < 2.3$
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days

##### GHS Hazards

H316	Causes mild skin irritation
H319	Causes serious eye irritation

##### GHS Precautions

P264	Wash ... thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention

---

Signal Word: Warning



Preexisting skin, eye, and respiratory disorders may be aggravated by exposure to this product.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Sodium tripolyphosphate	7758-29-4	5.00% - 10.00%
Alcohols, C9-11, ethoxylated	68439-46-3	1.00% - 5.00%
Disodium Metasilicate	6834-92-0	1.00% - 5.00%
b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl]-monosodium salt	64972-19-6	1.00% - 5.00%
Tetrasodium pyrophosphate	7722-88-5	1.00% - 5.00%

### 4. FIRST AID MEASURES

**INHALATION** - Take affected persons out into the fresh air. Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

**EYE CONTACT** - In case of eye contact, flush the eyes with water for fifteen (15) minutes. If contact lenses are worn, quickly remove them, then flush the eyes with water. Have a physician examine the eyes.

**SKIN CONTACT** - Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. Rinse until skin no longer feels slippery. If skin irritation continues, consult a doctor.

**INGESTION** - If material is ingested, rinse out mouth with water and seek immediate medical attention. Do not induce vomiting but if vomiting occurs spontaneously, keep the head below the hips to prevent aspiration of liquid into the lungs. If victim is conscious drink large quantities of water to dilute stomach contents.

Notes to Physician: If swallowed, gastric irrigation with added, activated carbon. If swallowed or in case of vomiting, danger of entering the lungs. If necessary oxygen respiration treatment.

### 5. FIRE FIGHTING MEASURES

Flash Point: 100C

LEL:

UEL:

**EXTINGUISHING MEDIA:** This product is not inherently flammable. Use media appropriate for surrounding fire.  
**UNUSUAL FIRE OR EXPLOSION HAZARDS:** The product vapor is heavier than air and may travel a considerable distance to a source of ignition and flashback.

**HAZARDOUS COMBUSTION PRODUCTS:** See section 10 for a list of hazardous decomposition products for this mixture.

**FIRE FIGHTING:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel

and equipment with a water wash-down after fire and smoke exposure.

**FIRE FIGHTING EQUIPMENT:** Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

**SPILL AND LEAK PROCEDURES:** Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Keep nonessential personnel away from the contaminated area. Spilled product may be very slippery!

**SMALL SPILLS:** Ventilate the contaminated area. Mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

**LARGE SPILLS:** Prevent this material from entering sewers and watercourses by diking or impounding the spilled material. Advise authorities if the product has entered or may enter, sewers, watercourses, or extensive land areas.

Ventilate the contaminated area. Mix the appropriate sorbent into the spilled material. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect the saturated sorbent and transfer it into a covered container. Steel containers are acceptable for all wastes except wastes which contain acid. Use suitable plastic containers for acid-bearing wastes.

Label the waste container. Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## 7. HANDLING AND STORAGE

**HANDLING PRECAUTIONS:** Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Avoid aerosolizing product. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

Do not allow product to come in contact with aluminum.

**STORAGE: Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

**· Information about storage in one common storage facility:**

Store away from foodstuffs.

Do not store together with acids.

**· Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

**REGULATORY REQUIREMENTS:** No data found.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium tripolyphosphate 7758-29-4	10 mg/m <sup>3</sup> TWA (total dust) 5 mg/m <sup>3</sup> TWA (respirable dust)	Not Established	Not Established
Alcohols, C9-11, ethoxylated 68439-46-3	Not Established	Not Established	Not Established
Disodium Metasilicate 6834-92-0	Not Established	Not Established	Not Established
b-Alanine, N-(2- carboxyethyl)-N-[3- (decyloxy)propyl]- monosodium salt 64972-19-6	Not Established	Not Established	Not Established
Tetrasodium pyrophosphate 7722-88-5	Z-1 Limits for Air Contaminants 1910.1000 TWA 5 mg/m <sup>3</sup>	Not Established	NIOSH Recommended Exposure Limits TWA 5 mg/m <sup>3</sup>

### ENGINEERING:

**VENTILATION:** Use only with adequate ventilation, i.e., ventilation in compliance with occupational exposure limits. Use mechanical ventilation to reduce buildup of vapors in enclosed areas.

**ADMINISTRATIVE CONTROLS:** Read SDS and follow recommended procedures.

**PROTECTIVE EQUIPMENT:** Wear splash goggles. If extra protection is required, wear a face shield over the splash goggles. Face shields are effective only if worn in addition to splash goggles.

Wear a chemical-resistant, butyl-rubber apron and other protective clothing, as deemed appropriate, to avoid skin contact with material.

Wear chemical-resistant gloves (butyl rubber or neoprene). Protective gloves should be inspected frequently and discarded when they exhibit cuts, tears, pinholes, or signs of excessive wear.

Respiratory protection may not be needed if the local exhaust is sufficient to maintain levels of hazardous ingredients below occupational exposure limits. If needed, use a NIOSH/MSHA approved respirator equipped with a full facepiece, organic vapor cartridges, and high-efficiency, particulate air (HEPA) filters. Do not use respirators beyond their capabilities. FOR EMERGENCIES AND UNKNOWN CONCENTRATIONS, use supplied-air respiratory protection or a positive-pressure, self-contained breathing apparatus (SCBA).

**CONTAMINATED EQUIPMENT:** Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

<b>Appearance:</b> Clear liquid	<b>Odor:</b> Very Mild
<b>Vapor Pressure:</b> 16.8 mmHg <b>Vapor Density:</b> 0.7 <b>Specific Gravity:</b> 1.11 <b>Freezing point:</b> No Data <b>Boiling range:</b> 99°C <b>Evaporation rate:</b> No Data <b>Explosive Limits:</b> 0%	<b>Odor threshold:</b> No Data <b>pH:</b> 13 <b>Melting point:</b> No Data <b>Solubility:</b> No Data <b>Flash point:</b> 100C <b>Flammability:</b> No Data <b>Partition coefficient (n-octanol/water):</b> No Data <b>Decomposition temperature:</b> No Data <b>Grams VOC less water:</b> No Data
<b>Autoignition temperature:</b> No Data <b>Viscosity:</b> No Data	

## 10. STABILITY AND REACTIVITY

Stability: Hazardous polymerization will not occur.

STABLE

Components of this mixture are incompatible with the following materials: Acids and soft metals like aluminum. .

This mixture is likely to exhibit the following combustion products:

Oxides of carbon and nitrogen

## 11. TOXICOLOGICAL INFORMATION

### Mixture Toxicity

### Component Toxicity

7758-29-4	Sodium tripolyphosphate Oral LD50: 3,120 mg/kg (rat) Dermal LD50: 4,640 mg/kg (rabbit)
68439-46-3	Alcohols, C9-11, ethoxylated Oral LD50: 2,001 mg/kg (rat) Dermal LD50: 3,300 mg/kg (rat)

Exposure to this material may affect the following organs:

### Effects of Overexposure

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

## 12. ECOLOGICAL INFORMATION

Ecological information: No data found.

### **Component Ecotoxicity**

Alcohols, C9-11, ethoxylated	Toxicity to fish - Components Alcohols, C9-11, ethoxylated LC50 (96 h) : 1 - 10 mg/l Species : Fathead minnow (Pimephales promelas). Toxicity to daphnia - Components Alcohols, C9-11, ethoxylated EC50 (48 h) : 1 - 10 mg/l Species : Daphnia Toxicity to algae - Components Alcohols, C9-11, ethoxylated ErC50 (96 h) : 1 - 10 mg/l Species : Algae.
b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl]- monosodium salt	Aquatic toxicity : (96 h) : 10 - 100 mg/l Species : Fathead minnow (Pimephales promelas).
Tetrasodium pyrophosphate	Toxicity to fish: LC50 - other fish - 1,380 mg/l, 96 h Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - 391 mg/l, 48 h

## 13. DISPOSAL CONSIDERATIONS

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

## 14. TRANSPORT INFORMATION

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
US DOT	Non Regulated			

## 15. REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed in MA RTK  
7722-88-5 Tetrasodium pyrophosphate 1 to 5 %

The following chemicals are on the NJ RTK list:  
7722-88-5 Tetrasodium pyrophosphate 1 to 5 %  
6834-92-0 Disodium Metasilicate 1 to 5 %

The following chemicals are on the PA RTK list  
7722-88-5 Tetrasodium pyrophosphate 1 to 5 %  
6834-92-0 Disodium Metasilicate 1 to 5 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
Canada	Canadian Domestic Substances List	Yes
US	Toxic Substances Control Act	Yes

### EU Risk Phrases

#### Safety Phrase

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

## 16. OTHER INFORMATION

### Hazardous Material Information System (HMIS)

HEALTH	<input type="text"/>	1
FLAMMABILITY	<input type="text"/>	1
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	

#### HMIS & NFPA Hazard Rating Legend

\* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

### National Fire Protection Association (NFPA)



**DISCLAIMER AND NON-WARRANTY:** This Safety Data Sheet was prepared by Bon Tool Co. and is correct to the best of our knowledge, information and belief at the date of its publication. The information came from raw material suppliers, regulatory databases, and/or third parties with expertise in this area. This information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. No warranties of any kind, either expressed or implied, including warranties of the accuracy of the information presented and the suitability of a product for a particular purpose

Reviewer Revision

Date Prepared: 6/3/2015