

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/04/2018

Revised On 01/04/2018

1. Identification of the substance and manufacturer

Trade Name: UTILITY YELLOW
Product Code: 0000200678
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 Phone: 815-895-9101 www.seymourpaint.com



Emergency telephone number: CHEM-TEL 1-800-255-3924, 813-248-0585 * if located outside of the U.S.*

2. Hazard(s) identification:

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 STOT SE 3 H335 May cause respiratory irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|-------------------|--------|
| 64742-89-8 | VM&P Naphtha | 17.97% |
| 74-98-6 | propane | 17.64% |
| 1317-65-3 | Calcium Carbonate | 15.85% |
| 106-97-8 | n-butane | 10.36% |
| 64742-47-8 | Mineral Spirits | 4.44% |

4. First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints
After Skin Contact: Remove contaminated clothing. Wash exposed area with soap and water.
After Eye Contact: Rinse opened eye for several minutes under running water. Then consult a doctor
After Swallowing: Rinse out mouth and then drink plenty of water
 Rinse mouth with water. Do not induce vomiting
Most Important Symptoms and Effects: Dizziness
Indication of any immediate Medical Attention Needed: No further relevant information available

5. Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

Safety Data Sheet

Printing date 01/04/2018

acc. to OSHA HCS

Revised On 01/02/2018

Trade name: UTILITY YELLOW

6. Accidental release measures
Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
 Use respiratory protective device against the effects of fumes/dust/aerosol

Methods and material for containment and cleaning up: Ensure adequate ventilation

7. Handling and storage:
Precautions for safe handling Use only in well ventilated areas
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in sub freezing conditions. Store locked up.

8. Exposure controls/personal protection

| Components with limit values that require monitoring at the workplace: | |
|--|--|
| 74-98-6 propane | |
| PEL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| TLV (USA) | refer to Appendix F in TLVs&BEIs book; D, |
| 106-97-8 n-butane | |
| REL (USA) | Long-term value: 1900 mg/m ³ , 800 ppm |
| TLV (USA) | Short-term value: 2370 mg/m ³ , 1000 ppm (EX) |

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.
 Wash hands after use.
 Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
 The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9. Physical and chemical properties

Appearance: Aerosol
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -44 °C (-47.2 °F)
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Extremely flammable
Decomposition temperature: Not determined
Auto igniting: Product is not self-igniting
Danger of explosion: In use, may form flammable/explosive vapour-air mixture
Lower Explosion Limit: 1.5 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density: Not determined
Evaporation rate: Not applicable
Partition coefficient: n-octanol/water: Not determined
Solubility: Not determined
Viscosity: Not determined
Water: 22.3 %

10. Stability and reactivity
Reactivity: Stable at normal temperatures
Conditions to avoid: Do not allow to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures
Chemical Stability: Not fully evaluated
Possibility of hazardous reactions: No dangerous reactions known
Incompatible materials: No further relevant information available
Hazardous decomposition: No dangerous decomposition products known

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/04/2018

Revised On 01/02/2018

Trade name: UTILITY YELLOW

| | | |
|---|------------------------------|----------------|
| 11. Toxicological information | | |
| LD/LC50 values that are relevant for classification: | | |
| 106-97-8 n-butane | | |
| Inhalative | LC50/4 h | 658 mg/l (rat) |
| Information on toxicological effects: | No data available | |
| Skin effects: | No irritant effect | |
| Eye effects: | No irritating effect | |
| Sensitization: | No sensitizing effects known | |

| | |
|---------------------------------------|--|
| 12. Ecological information | |
| Aquatic toxicity: | Hazardous for water, do not empty into drains |
| Persistence and degradability: | The product is degradable after prolonged exposure to natural weathering processes |
| Bioaccumulative potential: | No further relevant information available |
| Mobility in soil: | No further relevant information available |
| Other adverse effects: | No further relevant information available |

13. Disposal considerations
 Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

| | |
|---------------------------------------|--|
| 14. Transport Information | |
| UN-Number | UN1950 |
| DOT | N/A |
| DOT | Consumer Commodity ORM-D |
| ADR | Aerosols, flammable |
| Transport hazard class(es): | 1950 Aerosols |
| Class | 2.1 |
| Marine pollutant: | No |
| Special precautions for user: | Warning: Gases |
| Storage Code: | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| Quantity limitations | On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg |
| ADR | |
| Excepted quantities (EQ) Code: | E0 Not permitted as Excepted Quantity |
| IMDG | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) Code: | E0 Not permitted as Excepted Quantity |
| Packaging Group: | -- |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

| | |
|---|--|
| 15. Regulatory Information | |
| SARA Section 355 (extremely hazardous substances): | |
| None of the ingredients in this product are listed. | |
| SARA Section 313 (Specific toxic chemical listings): | |
| None of the ingredients is listed. | |
| Toxic Substances Control Act (TSCA): | |
| All hazardous ingredients for this product are found on the inventory list of substances. | |
| Consumer Product Safety Commission (CPSC): | |
| This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. | |

Trade name: UTILITY YELLOW

California Proposition 65 chemicals known to cause cancer:

| | |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
| 100-41-4 | ethyl benzene |

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

WHMIS Symbols for Canada: A - Compressed gas  

EPA: None of the ingredients listed

16. Other Information
Contact: Regulatory Affairs
Date of preparation / last revision 01/04/2018 / -