



#32-302 Exposed Aggregate Retarder

DESCRIPTION

EXPOSED AGGREGATE RETARDER is a concrete set retarder. Application of EXPOSED AGGREGATE RETARDER to freshly placed concrete allows for the removal of the top layer of paste, creating an exposed-aggregate finish for decorative concrete. EXPOSED AGGREGATE RETARDER contains a fugitive dye for easy monitoring of application rates.

EXPOSED AGGREGATE RETARDER is a concrete set retarder, designed for use on horizontal surfaces where an exposed aggregate finish is desired.

FEATURES

- * High Visibility
- * Bright Green Fugitive Dye makes it Easy to See
- * Easily Sprayable
- * Even Finish
- * Proven Formula

APPLICATION

Complete floating and troweling procedures and allow the surface's bleed water to disappear. Using an ordinary, low-pressure garden sprayer, uniformly apply EXPOSED AGGREGATE RETARDER to the surface without puddling. Cover the treated surface with plastic sheeting (preferably black) or continuously wetted burlap until the retarded paste is to be removed.

Allow the underlying concrete to set to the desired depth before attempting to remove the surface paste. The depth of retardation can be determined by probing the surface with a toothpick or steel wire.

Once the forms have been removed, usually 24-48 hours, spray the treated surface with a jet of water while scrubbing with a coarse floor brush to remove the retarded paste. Power washing is more efficient and should be used when possible. Test a small area to determine the depth of retardation before proceeding with the rest of the surface. If the depth is excessive, wait a while before washing. Sealer is recommended to brighten the color, prevent staining, and create a water-resistant surface.

NET COVERAGE RATE

100-150 ft² per gallon

TECHNICAL DATA

VOC: <350g/L
Flash Point: N/A

HMIS

Health	1	Flammability	0
Reactivity	0	Protection	B

CLEANUP

Clean tools with water.

PRECAUTIONS

If frozen, allow to thaw and mix thoroughly before using.

DISCLAIMER: *Since the manufacturer has no control over handling, use, or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor costs and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.*