



#42-349 Gloss Sealer

DESCRIPTION

GLOSS SEALER is a tough pure acrylic concrete sealer in a solvent base. It is designed to protect and beautify all types of concrete with a high gloss durable clear coating. GLOSS SEALER is non-yellowing to preserve the appearance of all types of decorative concrete. GLOSS SEALER is formulated as follows:

FEDERAL

<600 VOC Compliant: Available in 19% solids.

PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with a cleaner/degreaser. Use a bristle brush for heavily oiled spots. Rinse well with a pressure washer. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause bubbles to form. For pavers, sweep away any loose sand. DO NOT THIN.

APPLICATION

Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can or other metal container with appropriate roller. Use a long nap roller for exposed aggregate, a medium nap roller for textured surfaces and a short nap roller for smooth surfaces. Wait until the surface is tack-free before applying a second coat. Apply perpendicular to the first coat. Cross-rolling allows for an even application. If spraying, use a solvent resistant sprayer holding tip no more than 8" from surface during application. Back rolling is recommended while spraying. Clean up immediately with Xylene or Acetone. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Cooler temperatures or increased humidity will slow the dry time.

NET COVERAGE RATE: Two thin coats are recommended.

Smooth Troweled:	300 ft ² per gallon
Textured or Stamped:	200 ft ² per gallon
Uncured Broom Swept:	200 ft ² per gallon
Exposed Aggregate and Pavers:	100 ft ² per gallon

TECHNICAL DATA

VOC compliant: <700g/L
Flash point: 106°F

HMIS

Health	2
Flammability	2
Reactivity	0
Protection	B

BOSS GLOSS™ CURE & SEAL CLEAR ENHANCER-HIGH VOC VT Meets or Exceeds: ASTM C-309, Type I Class A & B; ASTM C-1315; AASHTO Spec M-148; EPA 40 CFR Part D

SLIP RESISTANCE

For additional slip resistance, apply one coat of GLOSS SEALER. Mix GATOR GRIP™ SLIP RESISTANT ADDITIVE into sealer and apply with second coat.

CLEANUP

Clean tools with A1 Solvent, Acetone or Xylene.

MAINTENANCE

Clean sealed surface with water only. Reseal surface no more than two years or as needed to prevent buildup of sealer.

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.